

Files are **LEGEND:** S = Standard, O = Optional, P = Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication and is subject to change without notice.

2009 Dodge Grand Caravan

FEATURE AVAILABILITY

	SE	SXT
EXTERIOR		
Antenna, fixed long-mast	S	S
Colors		
Inferno Red Crystal Pearl Coat, Light Sandstone Metallic Clear Coat, Modern Blue Pearl Coat, Bright Silver Metallic Clear Coat, Brilliant Black Crystal Pearl Coat, Stone White Clear Coat, Deep Crimson Crystal Pearl Coat, and Melbourne Green Pearl Coat	O	O
Defroster—Electric, rear window	S	S
Door Handles		
Body-color	S	S
Fascias		
Body-color	S	S
Rear fascia scuff pad	S	S
Grille		
Black with body-color surround	S	—
Black with bright surround	—	S
Lamps		
Halogen headlamps	S	S
Headlamp-off time delay	S	S
Fog lamps	—	S
Liftgate—Power	P	O/P
Mirrors—Outside rearview		
Power, heated fold-away	S	S
Body-color	—	S
Moldings		
Beltline – Black	S	S
Beltline – Bright	—	P
Bodyside – Body-color	S	—
Bodyside – Body-color with bright insert	—	S
Remote Start	P	P
Roof Rack—Black side rails with black crossbars	O	S
Wiper System		
Rear window wiper/washer	S	S
Windshield—Variable intermittent	S	S
Rain-sensitive windshield wipers	—	P

INTERIOR

Air Conditioning	S	—
With three-zone manual temperature controls	P	S
With three-zone automatic temperature controls and air filtering	—	P
Rear air conditioning with heater	P	S
Assist Handles	S	S
Auxiliary Power Outlets		
115-volt	P	S
12-volt DC, front and rear	S	S
Carpet—Floor and cargo area	S	S
Colors		
Dark Slate Gray seats	O	O
Medium Slate Gray seats	O	O
Light Shale seats	—	O
Console		
Floor console with four cup holders	S	S
Premium removable sliding front console with four cup holders	—	P
Overhead console	S	S
Rear overhead console with storage bins	—	S
Door Locks—Power	S	S
Door—Power sliding	P	S
Floor Mats—Easy-clean	S	S
Grocery Bag Hooks—Rear seatback	S	S
HomeLink universal home security system transceiver	—	S
Universal garage door opener	—	S
Illumination		
Entry illumination	S	S
Liftgate flood lamp	S	S
Front courtesy/map lights	S	—
Rear dome lamp	S	—
Courtesy door lamps	—	P
Front door storage illumination	—	P
Cup holder illumination	—	S
Overhead ambient surround lighting	—	S
Rear swiveling reading/courtesy lamps	—	S
Instrument Panel		
White-face instrument cluster with 120-mph primary speedometer	S	—
White-face instrument cluster with 120-mph primary speedometer and tachometer	P	S
Electronic Vehicle Information Center (EVIC) with trip computer	—	P
Satin silver bezel	—	S
Trip computer with temperature and compass	P	S
Mirror		

Day/night manual rearview	S	S
Automatic-dimming rearview mirror	—	P
Interior observation/conversation mirror with sunglass holder	S	S
Pedals		
Power adjustable	P	S
Seats		
Cloth, low-back bucket seats with head restraints	S	S
Stain Repel Seat Fabric	S	S
Leather-trimmed bucket seats	—	P
Stow 'n Go [®] second-row bucket seating and storage system	S	S
Second-row bench seat with integrated child safety seats	O	—
Swivel 'n Go [™] swiveling second-row bucket seats	O/P	O/P
Heated front seats	—	P
Heated second-row seats	—	P
Integrated child booster seat (available with Swivel 'n Go seats)	O	O
Eight-way power driver seat	—	S
Eight-way power driver and passenger seats	—	P
Power folding third-row 60/40 bench seat	—	P
Driver adjustable lumbar—Manual	—	S
Shift Knob—leather-wrapped	—	S
Sound Systems		
AM/FM radio with CD player and MP3 play capability	S	S
Four speakers	S	—
Six speakers	P	S
Nine speakers with subwoofer and 506-watt amplifier	—	O/P
uconnect studios SIRIUS Satellite Radio—Not available in Hawaii or Puerto Rico (first-year service provided by SIRIUS)	P	S
uconnect tunes with 30-gigabyte hard drive and touch screen with single-disc CD/DVD/MP3 player, AM/FM radio, six speakers and ParkView [™] Rear Back-up Camera	O/P	O
uconnect gps 30-gigabyte hard drive, navigation radio, including touch screen, voice commands, SIRIUS Satellite Radio and uconnect phone that is Bluetooth compatible and iPod interface	—	O
Speed Control	S	S
Steering Wheel		
Tilt steering column	S	S
Steering-wheel-mounted audio controls	—	S
Leather-wrapped	—	S
Storage		
Driver side umbrella holder	S	S
Glove boxes, dual	S	S
Lower instrument panel cubby bin	S	S
Map pockets, dual second-row	S	S
Bottle holders in sliding doors	S	S
Left rear quarter trim storage bin	S	S

Overhead storage – Four bins	—	S
Sun Roof—Power, with mini overhead console	—	O
Sun Visors—Driver and front passenger with mirror	S	—
Sun Visors—Driver and front passenger with illuminated mirror	—	S
uconnect phone that is Bluetooth compatible and iPod interface	—	P
Windows		
Sunscreen glass	S	S
Power, with driver express-up-down and passenger express-down	S	S
Power, second-row	S	S
Power, rear quarter vents	S	S
Window Shades—Second- and third-row	—	P
POWERTRAIN AND CHASSIS		
3.3L V-6 OHV engine with 4-speed automatic transmission	S	—
3.8L V-6 OHV engine with 6-speed automatic transmission	—	S
4.0L V-6 SOHC engine with 6-speed automatic transmission	—	O/P
Alternator		
140-amp	S	—
160-amp	P	S
Battery—600-amp, maintenance-free	S	S
Brakes—Power, four-wheel disc with ABS	S	S
Engine Block Heater	O	O
Engine Oil Cooler	—	P
Flex Fuel Vehicle (FFV)	S	—
Front-wheel Drive	S	S
Fuel Tank—20-gallon capacity	S	S
Remote Start	P	P
Steering—Power rack-and-pinion	S	S
Suspension		
Front – Independent MacPherson	S	S
Rear – Twist-beam axle with coil springs, track bar, gas-charged shock absorbers	S	S
Load leveling and height control	—	P
Sport Suspension	—	P
Traction Control	S	S
Tires		
P225/65R16 BSW All-season	S	S
P225/65R17 BSW All-season Touring	—	P
Compact spare tire	S	S
Wheels		
16-inch steel wheels with full wheel covers	S	—
16-inch aluminum wheels	P	S
17-inch aluminum wheels	—	P

SAFETY AND SECURITY		
Air Bags		
Advanced multi-stage driver and front passenger	S	S
Supplemental all-row side-curtain	S	S
Anti-lock Four-wheel Disc Brakes	S	S
Brake Assist	S	S
Electronic Stability Program (ESP)	S	S
Emergency Accident Response System (EARS)	S	S
HomeLink universal home security system transceiver	—	O
Horn—Dual note electric	S	S
Illuminated Entry	S	S
LATCH (Lower Anchors and Tethers for CHildren)	S	S
ParkSense® Rear Park Assist System	—	P
ParkView® Rear Back-up Camera	P	P
Remote Keyless Entry	S	S
Removable Rechargeable Flashlight	—	P
Seat Belts	S	S
Security Alarm	—	P
Sentry Key® Engine Immobilizer	S	S
Side Blind Spot Monitoring and Rear Cross Path System	—	P
Tip Start	S	S
Tire Pressure Warning Lamp in Instrument Cluster	S	S
Warning Lamps—Door ajar, low washer fluid	S	S
Warning Chime	S	S
PACKAGES		
Climate Group —Includes air conditioning with three-zone temperature control, rear air conditioning with heater, and 160-amp alternator	O/P	—
Entertainment Group I —Includes uconnect tunes with 30-gigabyte hard drive and touch screen with single-disc CD/DVD/MP3 player, AM/FM radio, six speakers, ParkView® Rear Back-up Camera, and uconnect studios with SIRIUS Satellite Radio with first-year subscription provided by SIRIUS; second-row overhead DVD console with nine-inch video screen; two wireless headphones; video remote control; and 115-volt auxiliary power outlet	O	—
Popular Equipment Group —Includes right and left power-sliding rear doors, power liftgate, power adjustable pedals, and Remote Start	O	—
Flexible Seating Group —Includes second-row Swivel 'n Go™ quad chairs which swivel 180 degrees rearward to face the third-row seats; removable and storable table for the second and third row; and "Swivel 'n Go" badge	O	O
Mopar Exterior Appearance Group —Includes bright door sills, premium floor mats with logo, splash guards and body-color running boards	O	O
Premium Group —Includes automatic temperature control with three-zone temperature control; rain-sensitive windshield wipers; power-folding third-row seat; nine-speaker sound system with subwoofer and 506-watt amplifier; uconnect phone that is Bluetooth compatible, iPod interface, and auto-dimming rearview mirror with integrated microphone	—	O
Heated Seating Group —Includes heated front- and second-row seats	—	O

Security Group —Includes security alarm; uconnect phone that is Bluetooth compatible, iPod interface, and auto-dimming rearview mirror with integrated microphone; ParkSense [®] Rear Park Assist System; and side Blind Spot Monitoring and Rear Cross Path system	—	O
Entertainment Group II —Includes second- and third-row nine-inch overhead DVD screens; two two-channel wireless headphones; switchable video remote control; uconnect tunes with 30-gigabyte hard drive and touch screen with single-disc CD/DVD/MP3 player, AM/FM radio; and ParkView [™] Rear Back-up Camera	—	O
Family Value Group —Includes removable center front-seat console; second- and third-row window shades; and Remote Start	—	O
Trailer Tow Group —Includes heavy-duty engine cooling with engine oil cooler, heavy-duty transmission oil cooler and heavy-duty radiator; load leveling and height control; and trailer tow wiring harness	—	O

2009 Dodge Grand Caravan

SPECIFICATIONS

Dimensions are in inches (millimeters) at curb weight with standard wheels and tires unless otherwise noted.

GENERAL INFORMATION

Body Style	Multipurpose vehicle
Assembly Plant	Windsor, Ontario, Canada, and Fenton, Mo. USA
EPA Vehicle Class	Multipurpose vehicle

ENGINE: 3.3-LITER OHV SMPI FFV V-6

Availability	Standard – SE
Type and Description	Six-cylinder, 60° V-type, liquid-cooled
Displacement	210.5 cu. in. (3301 cu. cm)
Bore x Stroke	3.66 x 3.19 (93 x 81)
Valve System	OHV, 12 valves, roller followers, hydraulic lifters
Fuel Injection	Sequential, multi-port, electronic
Construction	Cast-iron block, aluminum-alloy heads
Compression Ratio	9.3:1
Power (SAE net)	175 hp (131 kW) @ 5,000 rpm (53 bhp/liter)
Torque (SAE net)	205 lb.-ft. (278 N•m) @ 4,000 rpm
Max. Engine Speed	5,600 rpm
Fuel Requirement	Unleaded mid-grade, 87 octane (R+M)/2, and up to E85 ethanol
Oil Capacity	5 qt. (4.7L)
Coolant Capacity	13.36 qt. (12.64L) – standard 16.28 qt. (15.4L) – with rear heater
Emission Controls	Three-way catalytic converter, heated oxygen sensors, electronic EGR, and internal engine features ⁽¹⁾
Estimated EPA Fuel Economy mpg (City/Hwy), NAFTA Markets	17/24
Assembly Plant	Trenton Engine Plant, Trenton, Mich. USA
(1) Meets Federal Tier 2, Bin 5+ emission requirements; marketed in California, New York, Massachusetts, Vermont and Maine as LEV II (Low Emission Vehicle).	

ENGINE: 3.8-LITER OHV SMPI V-6

Availability	Standard – SXT
Type and Description	Six-cylinder, 60° V-type, liquid-cooled
Displacement	230.5 cu. in. (3778 cu. cm)
Bore x Stroke	3.78 x 3.43 (96 x 87)
Valve System	OHV, 12 valves, roller followers, hydraulic lifters
Fuel Injection	Sequential, multi-port, electronic
Construction	Cast-iron block, aluminum-alloy heads
Compression Ratio	9.6:1
Power (SAE net)	197 hp (147 kW) @ 5,200 rpm (51.8 bhp/liter)

Torque (SAE net)	230 lb.-ft. (312 N•m) @ 4,000 rpm
Max. Engine Speed	5,600 rpm
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	5 qt. (4.7L)
Coolant Capacity	16.28 qt. (15.4L)
Emission Controls	Three-way catalytic converter, heated oxygen sensors, electronic EGR, and internal engine features ⁽²⁾
Estimated EPA Fuel Economy mpg (City/Hwy), NAFTA Markets	16/23
Assembly Plant	Trenton Engine Plant, Trenton, Mich. USA
(2) Meets Federal Tier 2, Bin 5+ emission requirements; marketed in California, New York, Massachusetts, Vermont and Maine as ULEV II (Ultra-Low Emission Vehicle).	

ENGINE: 4.0-LITER SOHC 24-VALVE SMPI V-6

Availability	Optional – SXT
Type and Description	Six-cylinder, 60° bank angle, liquid-cooled, with three-plenum intake manifold, electronically controlled manifold tuning valve and short-runner valves
Displacement	241.2 cu. in. (3952 cu. cm)
Bore x Stroke	3.78 x 3.58 (96 x 91)
Valve System	SOHC, 24 valves, hydraulic, center-pivot roller rocker arms
Fuel Injection	Sequential, multi-port, electronic
Construction	Semi-permanent mold aluminum block with cast-iron liners and cast-aluminum heads
Compression Ratio	10.3:1 on mid-grade fuel
Power (SAE net)	251 hp (189 kW) @ 6,000 rpm (62.75 bhp/liter)
Torque (SAE net)	259 lb.-ft. (350 N•m) @ 4,100 rpm
Max. Engine Speed	6,000 rpm (electronically limited)
Fuel Requirement	Unleaded, 87 octane (R+M)/2
Oil Capacity	5.5 qt. (5.2L) SAE 10W-30
Coolant Capacity	16.28 qt. (15.4L)
Emission Controls	Manifold three-way catalytic converters, quad heated oxygen sensors and internal engine features
Estimated EPA Fuel Economy mpg (City/Hwy), NAFTA Markets	17/25
Assembly Plant	Trenton Engine Plant, Trenton, Mich. USA

TRANSAXLE: 41TE, AUTOMATIC FOUR-SPEED OVERDRIVE

Availability	Standard with 3.3L engine
Description	4-speed overdrive, adaptive electronic control, electronically modulated converter clutch
Gear Ratios	
1 st	2.842
2 nd	1.57
3 rd	1.0

4 th	0.69
Reverse	3.214
Final Drive Ratio	3.434
Overall Top Gear	2.37

TRANSAXLE: 62TE, AUTOMATIC SIX-SPEED OVERDRIVE

Availability	Standard with 3.8L and 4.0L V-6 engines
Description	6-speed, adaptive electronic control, electronically modulated torque converter clutch
Gear Ratios	
1 st	4.127
2 nd	2.842
3 rd	2.283
4 th	Upshift – 1.452 WOT kickdown – 1.570
5 th	1.0
6 th	0.690
Reverse	3.214
Transfer Ratio	0.95
Final Drive Ratio	3.246
Overall Top Gear	2.24

DRIVERTRAIN

Front-wheel Drive	Standard
-------------------	----------

ELECTRICAL SYSTEM

Alternator	140-amp – Standard SE 160-amp – Standard SXT, Available on SE
Battery	600 CCA, maintenance-free

DIMENSIONS AND CAPACITIES

General

Wheelbase	121.2 (3078.2)
Overhang — Front	37.6 (955.4)
Overhang — Rear	43.7 (1108.9)
Track — Front	65.5 (1663.2)
Track — Rear	64.8 (1645.0)
Overall Length	202.5 (5142.5)
Overall Width	76.9 (1952.2)
Overall Width with Mirrors	88.5 (2246.8)
Overall Height	68.9 (1750.1)
Liftover Height	24.4 (619.9)
Cargo Width at Wheelhouse	49.03 (1245.5)

Maximum Cargo Height	48.56 (1233.4) SE 46.16 (1172.4) SXT
Angle of Approach (curb load)	14.3°
Angle of Departure (curb load)	18.7°
Breakover Angle (curb load)	13.9°
Minimum Running Ground Clearance (curb load)	6.1 (154.7)
Fuel Tank Capacity, gal. (L)	20 (76)
Gross Vehicle Weight Rating (GVWR), lbs. (kg)	5700 (2585)
Towing Capacity, lbs. (kg)	1800 (818) – SE 3600 (1632.9) – SXT with Trailer Tow Prep Package
U.S. Curb Weight, wet lbs. (kg)	
3.3L Gasoline Engine	4321 (1960.6) — SE, automatic transaxle Weight Distribution % F/R — 56/44
3.8L Gasoline Engine	4483 (2038) — SXT, automatic transaxle Weight Distribution % F/R — 56/44
4.0L Gasoline Engine	4514 (2047.3) — SXT, automatic transaxle Weight Distribution % F/R — 56/44
ACCOMMODATIONS	
Seating Capacity — F/I/R	2/2/3
Seating Capacity — F/I/R	2/2/3
SAE Total Interior Passenger Volume, cu. ft. (cu. m)	163.5 (4.63)/156.1 (4.42)
Front	
Head Room	39.8 (1010.9)
Head Room with Sun Roof	37.2 (946.0)
Leg Room	40.6 (1031.7)
Shoulder Room	63.0 (1600.7)
Hip Room	57.0 (1446.9) SE 57.0 (1446.9) SXT
Seat Travel	8.7 (220)
Intermediate	
Head Room	39.2 (996.7) SE 39.7 (1008.1) SXT
Leg Room	36.4 (923.8) SE 36.3 (922.5) SXT
Knee Clearance	3.5 (88.9) SE 3.6 (92.7) SXT
Shoulder Room	64.7 (1643.4)
Hip Room	64.8 (1646.0) SE 64.8 (1647.1) SXT
Seat Travel, Optional Swivel 'n Go™ Seats	3.9 (100)
Intermediate Passenger Volume, cu. ft. (cu. m)	53.4 (1.51) SE

	54.0 (1.53) SXT
Rear	
Head Room	37.9 (961.9)
Leg Room	37.6 (954.6) SE 31.8 (807.9) SXT
Knee Clearance	37.6 (113.0)/31.8 (156.7)
Shoulder Room	62.0 (1575.9)
Hip Room	48.7 (1237.7)
Rear Passenger Volume, cu. ft. (cu. m)	51.1 (1.45) SE 43.2 (1.22) SXT
Cargo Volume	
Maximum Cargo Volume, cu. ft. (cu. m)	143.8 (4.07) SE 140.1 (3.97) SXT
Behind Second-row Seats, cu. ft. (cu. m)	82.7 (2.34) / 83.7 (2.37)
Aft of Third-row Seat, cu. ft. (cu. m)	32.3 (0.92)
Total Passenger plus Cargo Volume, cu. ft. (cu. m)	195.8 (5.54) SE 188.4 (5.34) SXT
BODY/CHASSIS	
Layout	Transverse front engine, front-wheel drive
Construction	Unitized steel with hinged front doors; sliding left and right side doors—power available; rear liftgate with gas props—power available
SUSPENSION	
Front	Independent MacPherson strut, coil over gas-charged shock absorbers, stabilizer bar with isolated suspension cradle
Rear	Twist-beam axle with coil springs, track bar, gas-charged shock absorbers; self-leveling shock absorbers included with Trailer Tow Package
STEERING	
Type	Power rack and pinion
Overall Ratio	16.9:1
Turning Diameter (curb-to-curb)	39.1 ft. (11.92 m)
Steering Turns (lock-to-lock)	3.14
BRAKES	
Power Assist Type	All—8 x 9 (204 x 320) tandem-diaphragm vacuum
Availability	U.S.—Standard on all models
Front	
Size and Type	11.9 x 1.1 (302 x 28) vented rotors with 42 mm single-piston IPB caliper
Swept Area (total front)	55.0 sq. in. (355 sq. cm)

Rear

Size and Type	12.0 x 0.47 (305 x 12) solid rotors with 42 mm single-piston IPB caliper
Swept Area (total rear)	54.3 sq. in. (350 sq. cm)
Parking Brake Type	Integral parking brake
Four-wheel Anti-lock (ABS)	Standard
Electronic Stability Program (ESP)	Standard
All-speed Traction Control	Standard

WHEELS (U.S.)

Availability	Standard—SE
Type and Material	Steel with painted bolt-on wheel cover
Size	16 x 6.5
Availability	Standard—SXT, Optional—SE
Type and Material	Machined-face cast-aluminum with painted pockets
Size	16 x 6.5
Availability	Optional—SXT
Type and Material	Machined cast-aluminum with painted pocket
Size	17 x 6.5

TIRES (U.S.)

Availability	Standard—SE and SXT
Size and Type	225/65R16, black sidewall, all season
Model	Yokohama Avid S33
Revs/per Mile (km)	763 (1230)
Availability	Optional—SXT
Size and Type	P225/65R17, black sidewall, all season touring
Model	Bridgestone Turanza EL400
Revs/per Mile (km)	736 (1187)